

Suggested Cameras for use with IRIS I.P. Systems
by Manufacturer by Model Number

Brand	Model	Box	Dome	Maximum Resolution **	Outdoor Use ***	Vandal Resistant	IR Illuminators	Horizontal Viewing Angle (Degrees)	Zoom	Focal Length	Day / Night	Power Requirements	Power (Max.)
IRIS	7100-01 (Camera)	Mini-Cam		758 x 540	No	No	No	70.5	Fixed	3.8mm	S/W - Pixim	12-24VAC/VDC	1.8W
IRIS	7910-01 (Encoder) *	Specialty		Varies	-	-	-	-	-	-	-	12-24VAC/VDC	1.8W
IRIS	1ATMC-PX w/Encoder	Micro-ATM		758 x 540	No	No	No	96.6	Fixed	2.9mm	S/W - Pixim	12-24VAC/VDC	1.8W
IRIS	1DMC-PX w/Encoder		X	758 x 540	Protected - IP65	No	No	71.5	Fixed	3.8mm	S/W - Pixim	12-24VAC/VDC	1.8W
IRIS	1DMC-PX-VF w/Encoder		X	758 x 540	Protected - IP65	No	No	83.2 - 24.6	3.9x	2.8 - 11.0mm	S/W - Pixim	12-24VAC/VDC	1.8W
IRIS	1HSC25-PX w/Encoder	Height Strip		758 x 540	No	No	No	115.5	Fixed	2.5mm	S/W - Pixim	12-24VAC/VDC	1.8W
IRIS	1HSC29-PX w/Encoder	Height Strip		758 x 540	No	No	No	96.6	Fixed	2.9mm	S/W - Pixim	12-24VAC/VDC	1.8W
IRIS	1SCF-PX w/Encoder	FDIC Sign		758 x 540	No	No	No	71.5	Fixed	3.8mm	S/W - Pixim	12-24VAC/VDC	1.8W
IRIS	1SCN-PX w/Encoder	NCUA Sign		758 x 540	No	No	No	71.5	Fixed	3.8mm	S/W - Pixim	12-24VAC/VDC	1.8W
IRIS	1TC##-PX w/Encoder	Tower		758 x 540	No	No	No	71.5	Fixed	3.8mm	S/W - Pixim	12-24VAC/VDC	1.8W
IRIS	1TC##ADJ-PX w/Encoder	Adj. Tower		758 x 540	No	No	No	71.5 (Adj.)	Fixed	3.8mm	S/W - Pixim	12-24VAC/VDC	1.8W

Axis	207W	X		640 x 480	No	No	No	55	Fixed	4.0mm	-	VDC	-
Axis	209FD		X	640 x 480	No	No	No	66	Fixed	3.0mm	-	PoE (Class 1)	-
Axis	209MFD		X	1280 x 1024	No	No	No	74	Fixed	3.6mm	-	PoE (Class 1)	-
Axis	210A	X		640 x 480	No	No	No	48	Fixed	4.0mm	-	7-20VDC	7W
Axis	211A	X		640 x 480	Req. Housing	No	No	67 - 27	2.7x	3.0 - 8.0mm	-	PoE (Class 2)	7W
Axis	212 PTZ		X	640 x 480	No	No	No	140 - 44	3x	2.7mm	-	VDC, PoE (Class 1)	-
Axis	212 PTZ-V		X	640 x 480	No	Yes	No	140 - 44	3x	2.7mm	-	VDC, PoE (Class 1)	-
Axis	214 PTZ		X	704 x 576	Req. Housing	No	No	48 - 2.7	18x	4.1 - 73.8mm	Automatic	VDC	14W
Axis	215 PTZ		X	704 x 480	Req. Housing	No	No	51.6 - 4.4	12.1x	3.8 - 46.0mm	Automatic	VDC	-
Axis	215 PTZ-E		X	704 x 480	Yes - IP66	No	No	51.6 - 4.4	12.1x	3.8 - 46.0mm	Automatic	VDC	-
Axis	216FD		X	640 x 480	No	No	No	73 - 20	3.6x	2.8 - 10.0mm	-	4.9-5.1 VDC, PoE (Class 1)	3.6W
Axis	216FD-V		X	640 x 480	No	Yes	No	73 - 20	3.6x	2.8 - 10.0mm	-	4.9-5.1 VDC, PoE (Class 1)	3.6W
Axis	216MFD		X	1280 x 1024	No	No	No	100 - 27	3.6x	2.8 - 10.0mm	-	VDC, PoE (Class 1)	-
Axis	216MFD-V		X	1280 x 1024	No	Yes	No	100 - 27	3.6x	2.8 - 10.0mm	-	VDC, PoE (Class 1)	-
Axis	221	X		640 x 480	Req. Housing	No	No	93 - 35	2.7x	3.0 - 8.0mm	Automatic	VDC, VAC, PoE (class 2)	-
Axis	225FD		X	640 x 480	Yes	Yes	No	75 - 36	2.1x	2.8 - 5.8mm	-	24VAC, 12VDC PoE (Class 2)	25W
Axis	232D+		X	704 x 480	Req. Housing	No	No	48 - 2.8	18x	4.1 - 73.8mm	Automatic	12-24VAC/VDC	-
Axis	233D		X	704 x 480	Req. Housing	No	No	55.8 - 1.73	35x	3.4 - 119.0mm	Automatic	12-24VAC/VDC	-
Axis	M1011	X		640 x 480	No	No	No	47	Fixed	4.4mm	-	VDC	-
Axis	M1011-W	X		640 x 480	No	No	No	47	Fixed	4.4mm	-	VDC	-
Axis	M1031-W	X		640 x 480	No	No	Yes	47	Fixed	4.4mm	-	VDC	-
Axis	M1054	X		1280 x 800	No	No	Yes	80	Fixed	2.9mm	-	VDC, PoE (Class 2)	-
Axis	M1103	X		800 x 600	Req. Housing	No	No	66	Fixed	2.8mm	-	PoE (Class 1)	-
Axis	M1104	X		1280 x 800	Req. Housing	No	No	80	Fixed	2.8mm	-	PoE (Class 1)	-
Axis	M1113	X		800 x 600	Req. Housing	No	No	65 - 25	2.8x	2.9 - 8.2mm	-	PoE (Class 1)	-
Axis	M1114	X		1280 x 800	Req. Housing	No	No	87 - 29	2.8x	2.8 - 8.0mm	-	PoE (Class 1)	-
Axis	M3011		X	640 x 480	No	No	No	66	Fixed	3.0mm	-	PoE (Class 1)	-
Axis	M3014		X	1280 x 800	No	No	No	80	Fixed	2.9mm	-	PoE (Class 1)	-
Axis	M3113-R		X	800 x 600	Yes	No	No	66	Fixed	2.9mm	-	PoE (Class 1)	-
Axis	M3114-R		X	1280 x 800	Yes	No	No	80	Fixed	2.9mm	-	PoE (Class 1)	-
Axis	M3203		X	800 x 600	No	No	No	66 - 18	3.6x	2.8 - 10.0mm	-	PoE (Class 2)	-
Axis	M3203-V		X	800 x 600	No	Yes	No	66 - 18	3.6x	2.8 - 10.0mm	-	PoE (Class 2)	-
Axis	M3204		X	1280 x 800	No	No	No	80 - 22	3.6x	2.8 - 10.0mm	-	PoE (Class 2)	-

Suggested Cameras for use with IRIS I.P. Systems

by Manufacturer by Model Number

Brand	Model	Box	Dome	Maximum Resolution **	Outdoor Use ***	Vandal Resistant	IR Illuminators	Horizontal Viewing Angle (Degrees)	Zoom	Focal Length	Day / Night	Power Requirements	Power (Max.)
Axis	M3204-V		X	1280 x 800	No	Yes	No	80 - 22	3.6x	2.8 - 10.0mm	-	PoE (Class 2)	-
Axis	P1311	X		640 x 480	Req. Housing	No	No	48	Fixed	4.0mm	-	8-20VDC, PoE (Class 1)	2.8W
Axis	P1343	X		800 x 600	No	No	No	59 - 25	2.7x	3.0 - 8.0mm	Automatic	8-20VDC, PoE (Class 2)	6.4W
Axis	P1343-E	X		800 x 600	Yes - IP66	No	No	59 - 25	2.7x	3.0 - 8.0mm	Automatic	High PoE	25.5W
Axis	P1344	X		1280 x 800	No	No	No	72 - 28	2.7x	3.0 - 8.0mm	Automatic	8-20VDC, PoE (Class 2)	6.4W
Axis	P1344-E	X		1280 x 800	Yes - IP66	No	No	72 - 28	2.7x	3.0 - 8.0mm	Automatic	High PoE	25.5W
Axis	P1346	X		2048 x 1536	No	No	No	61 - 29	2.5x	4.0 - 10.0mm	Automatic	8-20VDC, PoE (Class 3)	9.6W
Axis	P1346-E	X		2048 x 1536	Yes - IP66	No	No	61 - 29	2.5x	4.0 - 10.0mm	Automatic	High PoE	25.5W
Axis	P1347	X		2560 x 1920	No	No	No	77 - 28	2.8x	3.5 - 10.0mm	Automatic	8-20VDC, PoE (Class 3)	9.0W
Axis	P1347-E	X		2560 x 1920	Yes - IP66	Yes	No	77 - 28	2.8x	3.5 - 10.0mm	Automatic	High PoE	25.5W
Axis	P3301		X	640 x 480	No	No	No	72 - 23	3.6x	2.8 - 10.0mm	-	VDC, PoE (Class 1)	-
Axis	P3301-V		X	640 x 480	No	Yes	No	72 - 23	3.6x	2.8 - 10.0mm	-	VDC, PoE (Class 1)	-
Axis	P3304		X	1280 x 800	No	No	No	80 - 22	3.6x	2.8 - 10.0mm	-	VDC, PoE (Class 2)	-
Axis	P3304-V		X	1280 x 800	No	Yes	No	80 - 22	3.6x	2.8 - 10.0mm	-	VDC, PoE (Class 2)	-
Axis	P3343		X	800 x 600	No	No	No	72 - 34	2.4x	2.5 - 6.0mm	Automatic	VDC, PoE (Class 2)	-
Axis	P3343		X	800 x 600	No	No	No	54 - 17	5.5x	2.2 - 12.0mm	Automatic	VDC, PoE (Class 2)	-
Axis	P3343-V		X	800 x 600	No	Yes	No	72 - 34	2.4x	2.5 - 6.0mm	Automatic	VDC, PoE (Class 2)	-
Axis	P3343-V		X	800 x 600	No	Yes	No	54 - 17	5.5x	2.2 - 12.0mm	Automatic	VDC, PoE (Class 2)	-
Axis	P3343-VE		X	800 x 600	Yes - IP66	Yes	No	72 - 34	2.4x	2.5 - 6.0mm	Automatic	PoE (Class 3)	-
Axis	P3343-VE		X	800 x 600	Yes - IP66	Yes	No	54 - 17	3.6x	3.3 - 12.0mm	Automatic	PoE (Class 3)	-
Axis	P3344		X	1280 x 800	No	No	No	87 - 40	2.4x	2.5 - 6.0mm	Automatic	PoE (Class 2)	-
Axis	P3344		X	1280 x 800	No	No	No	70 - 20	3.6x	3.3 - 12.0mm	Automatic	PoE (Class 2)	-
Axis	P3344-V		X	1280 x 800	No	Yes	No	87 - 40	2.4x	2.5 - 6.0mm	Automatic	PoE (Class 2)	-
Axis	P3344-V		X	1280 x 800	No	Yes	No	70 - 20	3.6x	3.3 - 12.0mm	Automatic	PoE (Class 2)	-
Axis	P3344-VE		X	1280 x 800	Yes - IP66	Yes	No	87 - 40	2.4x	2.5 - 6.0mm	Automatic	PoE (Class 3)	-
Axis	P3344-VE		X	1280 x 800	Yes - IP66	Yes	No	70 - 20	3.6x	3.3 - 12.0mm	Automatic	PoE (Class 3)	-
Axis	P5532		X	720 x 480	Yes - IP51	No	No	53.1 - 2.0	29x	3.6 - 104.4mm	Automatic	VDC, VAC, High PoE	-
Axis	P5534 PTZ		X	1280 x 720	Yes - IP51	No	No	55.2 - 3.2	18x	4.7 - 84.6mm	Automatic	20-24VAC, 24-34VDC, PoE	30W
Axis	Q6032-E		X	720 x 480	Yes - IP66	No	No	55.8 - 1.73	35x	3.4 - 119.0mm	Automatic	High PoE	-
Axis	Q6034		X	1280 x 720	Req. Housing	No	No	55.2 - 3.2	18x	4.7 - 84.6mm	Automatic	VDC, VAC, High PoE	-
Axis	Q6034-E		X	1280 x 720	Yes - IP66	No	No	55.2 - 3.2	18x	4.7 - 84.6mm	Automatic	High PoE	-
Pelco	IP110-CWV22		X	720 x 540	Yes	Yes - IK10	No	32.4 - 13.6	2.4x	9.0 - 22.0mm	Day/Night	24VAC, PoE	14W
Pelco	IP110-CWV9		X	720 x 540	Yes	Yes - IK10	No	100.4 - 31.6	3.2x	3.0 - 9.5mm	Day/Night	24VAC, PoE	14W
Pelco	IP110-DWV22		X	720 x 540	Yes	Yes - IK10	No	32.4 - 13.6	2.4x	9.0 - 22.0mm	Day/Night	24VAC, PoE	14W
Pelco	IP110-DWV9		X	720 x 540	Yes	Yes - IK10	No	100.4 - 31.6	3.2x	3.0 - 9.5mm	Day/Night	24VAC, PoE	14W
Pelco	IP111-CWV22		X	720 x 540	Yes	Yes - IK10	No	32.4 - 13.6	2.4x	9.0 - 22.0mm	Day/Night	24VAC, PoE	14W
Pelco	IP111-CWV9		X	720 x 540	Yes	Yes - IK10	No	100.4 - 31.6	3.2x	3.0 - 9.5mm	Day/Night	24VAC, PoE	14W
Pelco	IP111-DWV22		X	720 x 540	Yes	Yes - IK10	No	32.4 - 13.6	2.4x	9.0 - 22.0mm	Day/Night	24VAC, PoE	14W
Pelco	IP111-DWV9		X	720 x 540	Yes	Yes - IK10	No	100.4 - 31.6	3.2x	3.0 - 9.5mm	Day/Night	24VAC, PoE	14W
Sony	SNC-CH110	X		1280 x 960	No	No	No	80.7	Fixed	2.34mm	Electrical D/N	PoE (Class 1)	2.4W
Sony	SNC-CH120	X		1280 x 1024	No	No	No	96.5 - 33.9	2.9x	2.8 - 8.0mm	Day/Night	PoE (Class 2)	5W
Sony	SNC-CH140	X		1280 x 1024	No	No	No	96.5 - 33.9	2.9x	2.8 - 8.0mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	9W
Sony	SNC-CH160	X		1280 x 1024	Yes - IP66	No	Yes	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 0)	12.9W

Suggested Cameras for use with IRIS I.P. Systems
by Manufacturer by Model Number

Brand	Model	Box	Dome	Maximum Resolution **	Outdoor Use ***	Vandal Resistant	IR Illuminators	Horizontal Viewing Angle (Degrees)	Zoom	Focal Length	Day / Night	Power Requirements	Power (Max.)
Sony	SNC-CH180	X		1280 x 1024	Yes - IP66	No	Yes	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	30W
Sony	SNC-CH210	X		2048 x 1536	No	No	No	88	Fixed	3.3mm	Electrical D/N	PoE (Class 1)	2.4W
Sony	SNC-CH220	X		1920 x 1440	No	No	No	101.2 - 47	2.1x	2.8 - 6.0mm	Day/Night	PoE (Class 2)	5W
Sony	SNC-CH240	X		1920 x 1440	No	No	No	101.2 - 47	2.1x	2.8 - 6.0mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	12.9W
Sony	SNC-CH260	X		1920 x 1440	Yes - IP66	No	Yes	88.5 - 32.3	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 0)	11.2W
Sony	SNC-CH280	X		1920 x 1440	Yes - IP66	No	Yes	88.5 - 32.3	2.9x	3.1 - 8.9mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	33W
Sony	SNC-DH110		X	1280 x 960	No	No	No	80.7	Fixed	2.34mm	Electrical D/N	PoE (Class 1)	2.4W
Sony	SNC-DH110T		X	1280 x 960	No	Yes - IK10	No	79	Fixed	2.34mm	Electrical D/N	PoE (Class 1)	2.4W
Sony	SNC-DH120		X	1280 x 1024	No	No	No	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 2)	6W
Sony	SNC-DH120T		X	1280 x 1024	No	Yes - IK10	No	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 2)	6W
Sony	SNC-DH140		X	1280 x 1024	No	No	No	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	10.2W
Sony	SNC-DH140T		X	1280 x 1024	No	Yes - IK10	No	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	8W
Sony	SNC-DH160		X	1280 x 1024	Yes - IP66	Yes - IK10	Yes	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 0)	12.9W
Sony	SNC-DH180		X	1280 x 1024	Yes - IP66	Yes - IK10	Yes	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	28W
Sony	SNC-DH210		X	2048 x 1536	No	No	No	88	Fixed	3.3mm	Electrical D/N	PoE (Class 1)	2.4W
Sony	SNC-DH210T		X	2048 x 1536	No	Yes - IK10	No	88	Fixed	3.3mm	Electrical D/N	PoE (Class 1)	2.4W
Sony	SNC-DH220		X	1920 x 1440	No	No	No	88.5 - 32.3	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 2)	6W
Sony	SNC-DH220T		X	1920 x 1440	No	Yes - IK10	No	88.5 - 32.3	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 2)	6W
Sony	SNC-DH240		X	1920 x 1440	No	No	No	88.5 - 32.3	2.9x	3.1 - 8.9mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	10.2W
Sony	SNC-DH240T		X	1920 x 1440	No	Yes - IK10	No	88.5 - 32.3	2.9x	3.1 - 8.9mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	10.2W
Sony	SNC-DH260		X	1920 x 1440	Yes - IP66	Yes - IK10	Yes	88.5 - 32.3	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 0)	12.9W
Sony	SNC-DH280		X	1920 x 1440	Yes - IP66	Yes - IK10	Yes	88.5 - 32.3	2.9x	3.1 - 8.9mm	Day/Night	24VAC, 12VDC, PoE (Class 0)	29W
Sony	SNC-EB520	X		800 x 600	No	No	No	89.2 - 34.6	2.6x	3.0 - 8.0mm	Day/Night	PoE (Class 2)	5W
Sony	SNC-EM520		X	800 x 600	No	No	No	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 2)	6W
Sony	SNC-EM521		X	800 x 600	No	Yes - IK10	No	85.4 - 31.2	2.9x	3.1 - 8.9mm	Day/Night	PoE (Class 2)	6W
Sony	SNC-EP520		X	720 x 480	No	No	No	57.8 - 1.7	36x	3.4 - 122.4mm	Day/Night	24VAC, HPoE (Class 4)	25W
Sony	SNC-EP550		X	1280 x 720	No	No	No	33.9 - 2.1	28x	3.5 - 98.0mm	Day/Night	24VAC, HPoE (Class 4)	25W
Sony	SNC-EP580		X	1920 x 1080	No	No	No	55.4 - 2.9	20x	4.7 - 94.0mm	Day/Night	24VAC, HPoE (Class 4)	25W
Sony	SNC-ER520		X	720 x 480	No	No	No	57.8 - 1.7	36x	3.4 - 122.4mm	Day/Night	24VAC, HPoE (Class 4)	25W
Sony	SNC-ER550		X	1280 x 720	No	No	No	33.9 - 2.1	28x	3.5 - 98.0mm	Day/Night	24VAC, HPoE (Class 4)	25W
Sony	SNC-ER580		X	1920 x 1080	No	No	No	55.4 - 2.9	20x	3.5 - 98.0mm	Day/Night	24VAC, HPoE (Class 4)	25W
Sony	SNT-EX101 (Encoder) *	Speciality		Varies	-	-	-	-	-	-	-	24VAC	-
Sony	SNT-EX101E (Encoder) *	Speciality		Varies	-	-	-	-	-	-	-	PoE (Class 2)	-

Previous Generation

Axis	213 PTZ	X		704 x 576	Yes	No	Yes	42 - 1.7	26x	3.5 - 91mm	Day/Night	11.5-14VDC	13W
Pelco	IP110-CHV22		X	768 x 494	Yes	Yes - IK10	No	30.6 - 13	3.2x	9.0 - 22.0mm	Day/Night	24VAC, PoE	14W
Pelco	IP110-CHV9		X	768 x 494	Yes	Yes - IK10	No	95 - 30.2	2.4x	3.0 - 9.5mm	Day/Night	24VAC, PoE	14W
Pelco	IP110-DNV22		X	768 x 494	Yes	Yes - IK10	No	30.6 - 13	3.2x	9.0 - 22.0mm	Day/Night	24VAC, PoE	14W
Pelco	IP110-DNV9		X	768 x 494	Yes	Yes - IK10	No	95 - 30.2	2.4x	3.0 - 9.5mm	Day/Night	24VAC, PoE	14W
Pelco	IP111-CHV22		X	768 x 494	Yes	Yes - IK10	No	30.6 - 13	3.2x	9.0 - 22.0mm	Day/Night	24VAC, PoE	14W
Pelco	IP111-CHV9		X	768 x 494	Yes	Yes - IK10	No	95 - 30.2	2.4x	3.0 - 9.5mm	Day/Night	24VAC, PoE	14W
Pelco	IP111-DNV22		X	768 x 494	Yes	Yes - IK10	No	30.6 - 13	3.2x	9.0 - 22.0mm	Day/Night	24VAC, PoE	14W

Suggested Cameras for use with IRIS I.P. Systems

by Manufacturer by Model Number

Brand	Model	Box	Dome	Maximum Resolution **	Outdoor Use ***	Vandal Resistant	IR Illuminators	Horizontal Viewing Angle (Degrees)	Zoom	Focal Length	Day / Night	Power Requirements	Power (Max.)
Pelco	IP111-DNV9		X	768 x 494	Yes	Yes - IK10	No	95 - 30.2	2.4x	3.0 - 9.5mm	Day/Night	24VAC, PoE	14W
Sony	SNC-CS11	X		659 x 494	No	No	No	94 - 35	2.7x	3.0 - 8.0mm	Day/Night	12VDC, 24VAC, PoE	5.4W
Sony	SNS-CS50N	X		768 x 494	No	No	No	94 - 35	2.7x	2.9 - 8.0mm	Day/Night	12VDC, 24VAC, PoE	9W
Sony	SNC-DF85N		X	640 x 480	Yes - IP66	Yes	No	100.8 - 27.7	3.6x	2.8 - 10.0mm	Day/Night	12VDC, 24VAC, PoE	10W
Sony	SNC-P1	X		640 x 480	No	No	No	53.4	Fixed	3.8mm	-	12VDC	3.5W

Notes

* Encoders will accept standard "analog" signal from majority of surveillance cameras, and convert video signal for use with I.P. Encoders listed will interface with IRIS Hybrid Systems.

** Performance of camera may be limited based on total DVR system configuration.

*** Outdoor use may require a weatherproof enclosure. Review manufacturer's specification sheet for more information.

IRIS's Pixim-based products carry a standard five-year (depot) warranty. Other products listed are warranted by their respective manufacturers.

Contents of this Chart may be changed without notice, including additions, revisions, or deletions. Manufacturers listed reserve the right to change specifications without notice.

No claims are made to the accuracy of the data presented in this table. For further information please review specifications available from each individual manufacturer listed