

IRIS DIGITAL VIDEO SYSTEMS

Introducing updated I.P. versions of our industry-leading Sign and Slim Tower Cameras. Law enforcement agencies around the country prefer the "up close" images captured by these cameras. Products support ONVIF Profile S standards.

The camera technology is designed to meet the flexibility and demands of any installation: True-HD 2.0MP technology, Motion Digital Zoom, and PoE just to name a few.

Our Adjustable Tower Camera is the perfect solution for capturing images through bullet resistive glass used in lobbies and drive-up areas. The Adjustable Tower Camera is designed to mount flush against the bullet resistive material, with adjustments minimizing lighting and glare issues.

The Tower Camera housing features a smaller footprint with a hidden mounting plate.



i.p.
sign & tower
cameras



Some of the applications for these cameras are:

Financial Institutions

- Teller stations
- Loan and new account desks
- ATMs
- Customer drive-thrus
- Lobby areas

Pharmacies / Grocery Stores

- Customer service areas
- Dispensary areas
- Cash handling areas
- General surveillance
- Customer drive-thrus

Retail / Restaurants

- Cash registers/points-of-sale
- Customer service areas
- General surveillance
- Customer drive-thrus

Car Rental Agencies

- Customer service counters
- Customer service booths
- Parking lot surveillance

Immigration/Airline


- Security check points

MDZ
MOTION DIGITAL ZOOM
TECHNOLOGY

Available on Specific Products

10750 Forest Lane
Dallas, Texas 75243
888.451.4646 • F 214.349.9429
www.iris-dvs.com

*IRIS products are
endorsed by leading
associations throughout
the United States!*




IRIS
DIGITAL VIDEO SYSTEMS

Specifications and Ordering Information

IP-Series	Sign-IP	Slim Tower-IP	Slim Adjustable Tower-IP
Part Number	FDIC: 3SCF-2M NCUA: 3SCN-2M Blank: 3SBN-2M	24": 3TC24-2M 20": 3TC20-2M 16": 3TC16-2M	3TC(##)ADJ-2M ① (##)=Height in Inches
Imager	2.1 MP Sensor		
Resolution	1920x1080, 1280x720, 720x576, 640x360, 320x180		
Interface	Network		
S/N Ratio	>52dB		
Minimum Illumination	0.01 Lux		
Bit Rate Type	Constant (CBR), Variable (VBR)		
Bit Rate	128 ~ 8092		
Network Transmission	ONVIF (Profile S)		
Compression	H.264 / M-JPEG / MPEG4		
Streams	H.264 / M-JPEG / MPEG4		
Frame Rates	Up to 30fps		
Lens	3.0mm		
Viewing Adjustments	External Positioning		Internal / External
Size - Width	8 5/8"	~ 2"	~ 2"
Size - Depth	2 1/8"	2 1/4"	2 1/4"
Size - Height	4 1/2"	Varies ②	Varies ③
Power Requirements	12VDC \pm 10%, ~ 4.0W Max. / PoE		
Operating Temp./Humidity	0°C ~ 50°C (32°F ~ 122°F), less than 90%, non-condensing		
Mounting Included	Bracket	Base	Base
Optional Signage	Yes	No	No
Finish - Powder Coat	Black		

Notes: 1. Internally Adjustable ~ \pm 20° (L-R), ~ \pm 15° (U-D). 2. Height varies by P/N. Custom lengths available. 3. Height of Adjustable Tower Camera (##) = 24" less height of counterline riser.



SCAN THE CODE TO VISIT US ON THE GO!



Actual Robbery Image

Law enforcement agencies will appreciate the up-close and high-detail images captured by the IRIS Sign and Tower Cameras.

Five-year product depot warranty provided by IRIS. Products are RoHS compliant.

© April 2019 – IRIS Digital Video Systems, Dallas, Texas. All rights reserved. IRIS is a registered trademark of The Security Center, Inc. Any other trademarks presented remain the property of their respective owners. IRIS products, including software and hardware, are protected by one or more of the following U.S. Patents: #D524,834; 9,380,256 B2; and others pending. In the interest of constant product improvement, features and options may change without notice.